

# Data sheet

## Drycoat Primer Glass

### 1-component glass primer.

<b>PROPERTIES</b>	1-component glass primer. Drycoat Primer Glass has the following properties:: <ul style="list-style-type: none"> <li>&gt; Fast-drying.</li> <li>&gt; Fast recoating time.</li> <li>&gt; Low viscosity.</li> <li>&gt; Colour: Transparent.</li> </ul>
<b>APPLICATIONS</b>	Drycoat Primer Glass is used as a primer on unpolished glass substrates under various Drycoat systems.
<b>PACK SIZE</b>	750 ml Single can.
<b>STORAGE</b>	Can be stored unopened and unmixed for approx. 12 months in a cool, dry place above freezing. Keep container away from direct sunlight when in storage and on the construction site.
<b>CONDITIONS FOR USE</b>	Drycoat Primer Glass can be applied at substrate and ambient temperatures between 0 °C and +35 °C. <p>Can be recoated after: approx. 15 min. at +20 °C  Can be recoated until: approx. 3 hrs. at +20 °C</p>
<b>PREPARATION OF THE SUBSTRATE</b>	The substrate must be sound, dry and free of ice, loose particles, grease and oil. Substrate adhesion must be tested on a case-by-case basis.
<b>MATERIAL CONSUMPTION</b>	Approx. 0.05 l/m <sup>2</sup> (50 ml) on a smooth, even surface



## 1-component glass primer

---